

## Żuraw przeznaczony dla wózków widłowych



### SPECYFIKACJA

#### CHARAKTERYSTYKA

1.1	Typ		CBFMXA-500-2.2	CBFMXA-500-2.7	CBFMXA-500-3.1	CBFMXA-500-3.5
1.2	Hak		Obrotowy	Obrotowy	Obrotowy	Obrotowy
1.3	Spadek udźwigu 1000 mm	[ kg ]	1400	1450	1900	2000
1.4	Spadek udźwigu 1250 mm	[ kg ]	1100	1200	1500	1600
1.5	Spadek udźwigu 1500 mm	[ kg ]	1000	1100	1200	1300
1.6	Spadek udźwigu 1750 mm	[ kg ]	850	900	1000	1100
1.7	Spadek udźwigu 2000 mm	[ kg ]	750	840	900	1000
1.8	Spadek udźwigu 2250 mm	[ kg ]	560	670	730	820
1.9	Spadek udźwigu 2500 mm	[ kg ]	440	490	580	670
1.10	Spadek udźwigu 2750 mm	[ kg ]	320	360	450	540
1.11	Spadek udźwigu 3000 mm	[ kg ]	230	270	370	460

#### WYMIARY

2.1	Dystans pomiędzy widłami	[ mm ]	496	546	546	546
2.2	Wymiary wideł	[ mm ]	125 x 50	150 x 50	150 x 50	150 x 50
2.3	Długość wysięgnika	[ mm ]	3000	3000	3000	3000

#### WAGA

3.1	Udźwig	[ kg ]	2500	3000	3500	4000
3.2	Waga	[ kg ]	282	330	332	332



